

UHF-SP2 TWO-WAY SPLITTER

- RF Branching Off Leaky Feeder Cable
- Compact Design
- N-Type Connectors
- 50 Ohm Impedance





FEATURES

The Becker Mining Systems' smartcom® 450 two-way splitter enables branching of Leaky Feeder cable and is a fully functional splitter for the frequencies 10 MHz - 2.7 GHz.

TECHNICAL DATA

PERFORMANCE SPECIFICATIONS		
Impedance	50 Ω	
Frequency Range	10 MHz - 2.7 GHz	
Isolation	30 dB avg	
RF Loss (nominal)	BR1 & BR2: 4 dB	
Voltage	Voltage Passing	
Max Current	2.2 A	

MECHANICAL DATA	
Dimensions (L x W x H)	84 x 67 x 23 mm (3.3 x 2.6 x 0.9 in)
Weight (nominal)	0.173 kg (0.381 lbs)
Enclosure	Aluminum
Connectors	N-type Jack

ENVIRONMENTAL DATA	
Temperature	65 to +85 °C
Range	(-85 to +185 °F)

APPROVALS	
RoHS Compliant	Yes

Technical data are limit values.

If the product is integrated into systems or operated in combination with other devices, its permissible operating values can deviate from these limit values. Subject to technical modifications without prior notice.

Rev. E





Tel +1 705 674 8111 Fax +1 705 674 7834

Becker Varis 122 Dell Street, Unit A Sudbury, Ontario Canada, P3C 2Y1

info@ca.becker-mining.com www.becker-mining.com